

Our VCMA-20ULS-PRO pump effectively delivers high-efficiency condensate removal from air conditioners, gas furnaces, and condensing boilers.

Item: 554630

Model: VCMA-20ULS-PRO

Ratings

HP	1/30 hp
Frequency	60 Hz
Amps - Full Load	1.5 A
Full Load Watts	93 W
Volts	115 VAC
Cord Length	6 ft
Continuous Duty	No
Maximum Flow Rate - 60Hz	1.4 gpm / 84 gph
Flow Rate At 1ft	1.4 gpm / 84 gph
Max PSIG	9.1 PSI
Max Flow Rate - 50Hz	1.4 gpm / 84 gph
Shut-Off	21 ft
Safety Switch	Yes

Liquid

Max Fluid Temperature	140 °F
-----------------------	--------

Materials of Construction

Check Valve	Yes
-------------	-----

Installation

Discharge	0.38 "
Product Length	10.23 "
Product Width	4.75 "
Product Height	6.46 "
Product Weight	5.5 lb
Product Weight w/ Pack	5.5 lb
Carton Length	12 "
Carton Width	4.81 "
Carton Height	6.44 "
Tubing Included	No

Other

Accessories / Repair Kits	Tank 154390_x000D_ Rubber Feet 925047_x000D_ Check Valve 3/8" 154724_x000D_ Tank Bracket 154483_x000D_ T-20/25 One carton of 25 pieces of 20' (6.01m) length 3/8" (9.5 mm) ID VC tubing 599033_x000D_ T-3/8 100' (640.1 m) of 3/8" (9.5 mm) ID x1/2" (12.37 mm) OD clear tubing 599107_x000D_ CV-X38 3/8" (9.5 mm) OD rigid plastic or copper tubing 599058_x000D_ Anti-Sweat Sleeve 10000014026_x000D_ Check Valve 1/4" OD 154725
---------------------------	--

Agency Approvals

CSA/UL

