

18V X2 LXT® LITHIUM-ION BRUSHLESS CORDLESS POWER-ASSISTED WHEELBARROW, TOOL ONLY



AVAILABLE IN SEPTEMBER AS KIT: XUC01PTX1



NEW TOOL OVERVIEW XUC01X1

LXT® X2 18V + 18V 36V BRUSHLESS

FEATURES

- Makita-built BL™ Brushless Motor for optimal performance
- Reversible for versatility and convenience
- Maximum load capacity up to 275 lbs.
- Rear wheel spacing is adjustable from 19" to 30" to accommodate the work environment
- L.E.D. lights on each side of frame to illuminate the work area
- L-shaped legs can be easily installed to replace rear wheels

SPECIFICATIONS

Speed Forward (High/Low MPH)	2.5 / 1 MPH
Speed Reverse (MPH)	.62 MPH
Max. Load Capacity	275 lbs.
Max. Grade	12°
Battery	2X 18V LXT® Lithium-Ion
Dimensions (LxWxH)	43-3/4" x 23-1/4" x 32-1/4"
Net Weight	87.2 lbs.
Shipping Weight	91.2 lbs.
UPC Code	088381-856423

STANDARD EQUIPMENT

- Steel Bucket (198494-2)
- 18V X2 LXT® Lithium-Ion Brushless Power-Assisted Hand Truck/ Wheel Barrow (XUC01Z)

XUC01PTX1 ALSO INCLUDES:

- 18V LXT® Lithium-Ion 5.0Ah Battery, 2/pk (BL1850-2)
- 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)

PRODUCT HIGHLIGHTS

RUN TIME

Delivers up to 60 minutes of run time using one 18V LXT® 6.0Ah BL1860 battery (battery not included)



POWER

2-speed with maximum speed up to 2.5 MPH on a 12° incline



INNOVATION

Holds (2) 18V LXT® batteries but operates using (1) 18V battery at a time (batteries not included)



CONVENIENCE

Interchangeable steel bucket or steel tube flat bed (flat bed optional)



RELATED ACCESSORIES

1. Steel Bucket (198494-2)
2. Flatbed Pipe Frame (199116-7)
3. 18V LXT® Lithium-Ion 6.0Ah Battery, 2/pk (BL1860B-2)
4. 18V LXT® Lithium-Ion Dual Port Charger (DC18RD)
5. ImpactX™ 35 Pc. Driver Bit Set (A-98326)

1

2

3

4

5

