



CAW Aluminum Series

Industrial Cold Water Pressure Washers



Electric — Wall-Mount — Direct Drive



CAW-2004-0ME1

Designed as a wall-mount, this series can be used in a wide range of locations. Featuring a non-corrosive aluminum frame, it is perfect for high volume cleaning and sanitizing.

PUMP

- Factory preset stainless-steel and brass trapping unloader
- Forged brass manifold
- Thermal relief valve
- External quick connect low pressure detergent injector
- Pump accepts incoming water up to 165°F (175°F on CAW-4004-0ME1)

MOTOR

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 4-foot power cord

FRAME

- Aluminum frame with wall-mounting brackets

COMPONENTS

- Time delay shutdown
- Remote mounted electrical box, must be mounted within 3½-feet of unit

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking hose
- 36-inch adjustable dual lance with insulated trigger gun (48-inch lance on CAW-4004-0ME1)

LIMITED WARRANTIES

- 1 year electric motor
- 7 year General pump



CAW Aluminum Series

Cold Water – Electric – Wall-Mount – Direct Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	UNLOADER	PLUG TYPE	DIMENSIONS (LxWxH)*	SHIP WT.	NET WT.
CAW-2004-OME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	General	Factory preset	NEMA 6-30P	31x17.25x18in.	248 lb.	188 lb.
CAW-2004-OME3	2000	3.9	6.0 HP, 230V, 3Ø, 16.4A	General	Factory preset	NEMA L15-20P	31x17.25x18in.	223 lb.	163 lb.
CAW-3004-OME1	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	Factory preset	NEMA 6-50P	31x17.25x18in.	268 lb.	208 lb.
CAW-3004-OME3	3000	3.9	8.0 HP, 230V, 3Ø, 22.8A	General	Factory preset	NEMA L15-30P	31x17.25x18in.	253 lb.	193 lb.
CAW-4004-OME1	4000	4.0	10.0 HP, 230V, 1Ø, 40.8A	General	Factory preset	NEMA 6-50P	34x18x19in.	368 lb.	293 lb.

*Dimensions do not include the mounting brackets.

ACCESSORY AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/8-inch non-marking hose – For when you need extra hose for added mobility	All models
CX-0078	Remote box – Adds control box, may be mounted away from unit to control on/off	All models
CX-0109	Additional remotes, up to 3 qty. – Additional remotes that may be added to unit after the first remote is installed; requires remote box option CX-0078	All models
CX-0110	460V on 6.0-HP, 3Ø model – When 460V of power is available	CAW-2004-OME3
CX-0111	460V on 8.0-HP, 3Ø model – When 460V of power is available	CAW-3004-OME3
CX-0112	Auto start/stop – When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models



NEMA L15-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug



CAW-2004-OME1

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.