



# CW Premium Series

Industrial Cold Water  
Pressure Washers

Gasoline — Portable — Belt Drive



CW-3504-5MGH

*Known as the workhorse of the industrial pressure washer line, this durable pressure washer takes cleaning to the next level and is built for extended cleaning applications.*

#### PUMP

- External bypass system protects from heat build-up
- Factory preset stainless-steel and brass unloader (CW-3504 and CW-4004 models feature Mi-T-M unloader)
- Forged brass manifold (Nickel plated brass on CW-4004 models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

#### ENGINE

- Performance-proven OHV engine with low-oil shutdown

#### FRAME

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Two-piece belt guard
- 13-inch flat-free tires

#### COMPONENT

- Heavy-duty dual cogged belt drive system

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking high pressure hose
- 48-inch lance with rubber grip (36-inch on CW-2505 and CW-3004 models)
- Professional-grade insulated trigger gun with safety lock-off

#### LIMITED WARRANTIES

- 1 year Mi-T-M unloader (CW-3504 and CW-4004 models)
- 3 year Honda, Kohler, Mi-T-M and Vanguard engines
- 7 year General pump

#### CERTIFICATION

- Intertek Certified to UL-1776 – US only (Honda and Vanguard engine models)



# CW Premium Series

## Cold Water – Gasoline – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH	2500	4.4	389cc Honda GX390 OHV <sup>+</sup>	General	45.5x28x26in.	290 lb.	216 lb.
CW-2505-4MGK	2500	4.4	429cc Kohler CH440 OHV	General	45.5x28x26in.	290 lb.	216 lb.
CW-2505-4MGM	2500	4.4	420cc Mi-T-M OHV	General	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH	3000	3.5	389cc Honda GX390 OHV <sup>+</sup>	General	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGK	3000	3.5	429cc Kohler CH440 OHV	General	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGM	3000	3.5	420cc Mi-T-M OHV	General	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH	3500	3.8	389cc Honda GX390 OHV <sup>+</sup>	General	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGK	3500	3.8	429cc Kohler CH440 OHV	General	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGM	3500	3.8	420cc Mi-T-M OHV	General	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH	4000	3.5	389cc Honda GX390 OHV <sup>+</sup>	General	46x28x30in.	290 lb.	216 lb.
CW-4004-5MVO	4000	4.0	480cc Vanguard OHV with electric start – battery not included	General	46x28x30in.	330 lb.	256 lb.

<sup>+</sup>49 state engine. Not for sale in California.

### ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/8-inch non-marking hose – High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	CW-2505 & CW-3004 models
CX-0045	Electric start – sealed battery included	All Honda engine models
CX-0054	Roll cage – Designed to protect equipment, comes with a lifting hook, 1/4-inch powder coated steel tubing	All Honda, Kohler and Mi-T-M engine models
CX-0055	Roll cage – Designed to protect equipment, comes with a lifting hook, 1/4-inch powder coated steel tubing	CW-4004-5MVO



CW-3504-5MGH

**⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**