

SPECIFICATIONS

MODEL NUMBER	CM-3200-0MMB
Operating Pressure (PSI/Bar):	3200/220.6
High Pressure Nozzle:	3.0
Water Volume (GPM/lpm):	2.4/9.1
Engine:	Mi-T-M
Displacement (cc)	212
Engine Type	4 Stroke, Overhead Valve, Single Cylinder
Oil Type	SAE10W-30
Oil Capacity (oz./liters)	20/.6
Fuel Type	Unleaded Gasoline 86 Octane Minimum
Fuel Capacity (gallon/ liters)	.95/3.6
Starting	Recoil
Maximum No Load RPM	3700 (+/- 100) RPM
Pump:	Axial Direct Driven, Oil Bath, Triplex Piston
Oil Type	Mi-T-M Pump Oil AW-4085-0016
Oil Capacity (oz./liters)	16/.47
Plungers	Ceramic Coated
Manifold	Forged Brass
Valves	Stainless Steel
Unloader	Preset
Detergent Injector	Low pressure downstream from pump
Unit Net Weight (lbs/Kg)	93/42.2
Unit Shipping Weight (lbs/Kg)	102/46.3
Unit Net Dimension (in/cm)	23.21Lx20.14Wx21.49H/ 58.95Lx51.16Wx54.58H
Unit Shipping Dimension (in/cm)	29.375Lx20.625Wx27.5H/ 74.61Lx52.39Wx69.85H
*Shipped without handle attached.	