

Job Name:	
System Reference:	Date:



Indoor Unit: PLA-A18BA6



Outdoor Unit: PUZ-A18NHA6 (-BS)

UNIT OPTION:

- ☐ Standard Model.....PUZ-A18NHA6
☐ Seacoast (BS) Model.....PUZ-A18NHA6-BS

ACCESSORIES:**Indoor Unit**

- ☐ Condensate Pump (BlueDiamond X87-711/721; 115/230V)
☐ Condensate Pump (Saueremann SI30-115/230; 115/230V)
☐ iSee Corner Panel (PAC-SA1ME-E)
☐ Multifunction Casement / MERV 10 Filter (PAC-SH53TM-E / PAC-SH59KF)
☐ Air Outlet Plates (PAC-SH51SP-E)

Outdoor Unit

- ☐ Wind Baffle (WB-PA1)*
 *Allows operation to 0° F (-18° C).
☐ Air Outlet Guide (PAC-SG58SG-E)
☐ Mounting Base (QSMS1201)
☐ Wall Bracket (QSWB2000M-1)

Controls

- ☐ Wireless Controller (MHK1)
☐ Advanced Wired Controller (PAR-31MAA)
☐ Simple Wired Controller (PAC-YT53CRAU)
☐ M-NET Adapter (PAC-SF83MA-E)
☐ Temperature Sensor (PAC-SE41TS)

SPECIFICATIONS:

Rated Conditions (Capacity / Input)*		
Cooling	Btu/h / W	18,000 / 1,940
Heating at 47° F	Btu/h / W	19,000 / 1,900
Heating at 17° F	Btu/h / W	13,000 / 1,590

* Rating Conditions per AHRI Standard:
 Cooling | Indoor: 80° F (27° C)DB / 67° F (19° C)WB; Outdoor: 95° F (35° C)DB / 75° F (24° C)WB
 Heating at 47° F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB; Outdoor: 47° F (8° C)DB / 43° F (6° C)WB
 Heating at 17° F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB; Outdoor: 17° F (-8° C)DB / 15° F (-9° C)WB

Capacity Range		
Cooling	Btu/h	8,000 - 18,000
Heating at 47° F	Btu/h	8,000 - 20,000

Operating Range	
Cooling	0° F** to 115° F (-18° C to 46° C) DB
Heating	12° F to 70° F (-11° C to 21° C) DB

** The minimum temperature will be 23° F (-5° C) DB if optional wind baffle accessory is not installed.

AHRI Efficiency Ratings	
EER	9.3
SEER	14.2
HSPF	9.8
COP at 47° F	2.93
COP at 17° F	2.40

Electrical Power Requirements	208 / 230V, 1-Phase, 60 Hz
-------------------------------	----------------------------

Minimum Circuit Ampacity (MCA)		
Indoor / Outdoor	A	1 / 13

Indoor Unit		
Fan Motor (ECM)	F.L.A.	0.51
Fan Motor Output	W	50
SHF / Moisture Removal		0.81 / 3 pt./h
Drain Lift Mechanism (Included)	H: In.	33-7/16

Outdoor Unit		
Compressor		DC INVERTER-driven Twin Rotary
Fan Motor (ECM)	F.L.A.	0.35
MOCP	A	20

Airflow Rate (Low-M1-M2-Hi)			
Indoor (Cooling)	DRY	CFM	420-490-570-640
	WET		390-460-530-600
Outdoor	DRY		1,200

Sound Pressure Level			
Indoor (Low-M1-M2-Hi)		dB(A)	28-29-31-32
Outdoor	Cooling		48
	Heating		47

External Dimensions		
Indoor (H x W x D)	In.(mm)	10-3/16 x 33-1/16 x 33-1/16 (258 x 840 x 840)
Outdoor (H x W x D)		23-5/8 x 31-1/2 x 11-13/16 + 7/8 (600 x 800 x 300 + 23)

Net Weight		
Indoor (Unit / Grille)	Lbs.(kg)	49 / 13 (22 / 6)
Outdoor		89 (40)

External Finish	
Indoor	Munsel No. 6.4Y 8.9/0.4
Outdoor	Munsell No. 3Y 7.8 / 1.1

Refrigerant	R410A ; 3lbs., 12oz.
-------------	----------------------

Refrigerant Piping (Flared)		
Liquid (High Pressure)	In.(mm)	1/4 (6.35)
Gas (Low Pressure)		1/2 (12.7)
Maximum Total Refrigerant Pipe Length	Ft. (m)	165 (50)
Maximum Vertical Separation	Ft. (m)	100 (30)

