



IMPACT WRENCHS

■ AT-5030

3/8" BUTTERFLY AIR IMPACT WRENCH

Specifications:

Drive	3/8"
Bolt Capacity	3/8"
Free Speed	10000 RPM
Max. Torque	75 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	3 CFM
Net Weight	1.8 lbs



63608475007

■ AT-5340

1/2" AIR IMPACT WRENCH

Specifications:

Drive	1/2"
Bolt Capacity	5/8"
Free Speed	6500 RPM
Max. Torque	400 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	4.2 CFM
Net Weight	6.2 lbs



636084751462

■ AT-5033

3/8" AIR IMPACT WRENCH

Specifications:

Drive	3/8"
Bolt Capacity	3/8"
Free Speed	9000 RPM
Max. Torque	75 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	3 CFM
Net Weight	2.4 lbs



636084750045

■ AT-5342

1/2" AIR IMPACT WRENCH

Specifications:

Drive	1/2"
Bolt Capacity	3/4"
Free Speed	9000 RPM
Max. Torque	550 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	4 CFM
Net Weight	6.8 lbs



636084751479

■ AT-5133

3/8" HEAVY DUTY AIR IMPACT WRENCH

Specifications:

Drive	3/8"
Bolt Capacity	7/16"
Free Speed	7000 RPM
Max. Torque	200 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	3 CFM
Net Weight	2.97 lbs



636084750106

■ AT5060L

3/4" AIR IMPACT WRENCH

Specifications:

Drive	3/4"
Bolt Capacity	1"
Free Speed	5000 RPM
Max. Torque	500 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	14.5 CFM
Net Weight	10.6 lbs



636084753190

■ AT-5040

1/2" AIR IMPACT WRENCH

Specifications:

Drive	1/2"
Bolt Capacity	5/8"
Free Speed	7000 RPM
Max. Torque	230 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	4 CFM
Net Weight	5.3 lbs



636084751134

■ AT-5162

3/4" IMPACT WRENCH

Specifications:

Drive	3/4"
Bolt Capacity	1-1/8"
Free Speed	5000 RPM
Max. Torque	1000 ft-lbs
Air Inlet	3/8" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	7 CFM
Net Weight	12.15 lbs



636084753206

IMPACTWRENCH, RATCHET WRENCHS & SANDERS

■ AT-5281L

1" AIR IMPACT WRENCH- 8" ANVIL

Specifications:

Drive	1"
Bolt Capacity	1-1/2"
Free Speed	3500 RPM
Max. Torque	1600 ft-lbs
Air Inlet	1/2" NPT
Air Pressure	90 PSI
Air Hose	1/2" (ID)
Air Consumption @ 90 PSI	23.5 CFM
Net Weight	24.2 lbs



636084754418

■ AT-7014

6" DUAL ACTION SANDER

Specifications:

Orbital Stroke	5 mm
Free Speed	10000 RPM
Pad Size	6"
Spindle Thread	5/16" - 24 UNF
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	4.25 lbs



636084772009

■ AT-5051

1/4" AIR RATCHET WRENCH

Specifications:

Drive	1/4"
Bolt Capacity	1/4"
Free Speed	240 RPM
Max. Torque	15 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	5/16" (ID)
Air Consumption @ 90 PSI	3 CFM
Net Weight	1.1 lbs



636084755002

■ AT-7012

5" HIGH SPEED SANDER

Specifications:

Free Speed	18000 RPM
Pad Size	5"
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	4 CFM
Net Weight	2.7 lbs



636084770333

■ AT-5052

3/8" AIR RATCHET WRENCH

Specifications:

Drive	3/8"
Bolt Capacity	3/8"
Free Speed	160 RPM
Max. Torque	50 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	4 CFM
Net Weight	2.4 lbs



636084755019

■ AT-7018

AIR ORBITAL SANDER

Specifications:

Free Speed	8000 RPM
Pad Size	3-2/3" x 6-3/4"
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	4.33 lbs



636084770432

■ AT-5054

1/2" AIR RATCHET WRENCH

Specifications:

Drive	1/2"
Bolt Capacity	1/2"
Free Speed	150 RPM
Max. Torque	90 ft-lbs
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	10 CFM
Net Weight	4.4 lbs



636084755088

■ AT-7019

STRAIGHT LINE SANDER

Specifications:

Free Speed	2500 SPM
Pad Size	16" x 2-1/2"
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	6.82 lbs



636084770463

GRINDERS, GREASE GUN & ACCESSORIES

■ AT-7231

1/4" MINI DIEGRINDER



Specifications:

Collet Size.....	1/4"
Free Speed.....	25000 RPM
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	4 CFM
Net Weight.....	0.77 lbs

636084772108

■ AT-7036

4" AIR ANGLE GRINDER



Specifications:

Collet Size.....	4"
Free Speed.....	11000 RPM
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	7.5 CFM
Net Weight.....	4.0 lbs

636084771166

■ AT-7232

1/4" MINI ANGLE DIE GRINDER



Specifications:

Collet Size.....	1/4"
Free Speed.....	18000 RPM
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	4 CFM
Net Weight.....	0.99 lbs

636084772146

■ AT-6036

AIR GREASE GUN



Specifications:

Capacity.....	400cc
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	6 CFM
Net Weight.....	3.9 lbs

636084760518

■ AT-7139

1/4" HIGH SPEED MINI DIE GRINDER



Specifications:

Collet Size.....	1/4"
Free Speed.....	18000 RPM
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	4 CFM
Net Weight.....	0.9 lbs

636084772030

■ TP- 6036A

10" FLEXIBLE GREASE HOSE



For use with AT-6036 Air Grease Gun.

636084787232

■ AT-7139K

1/4" HIGH SPEED MINI DIE GRINDER KIT



Contains:

- 1 pc AT-7139 Air Die Grinder
- 1 pc 1/8" Collet
- 5 pc 1/4" Shank Mounted Stone
- 5 pc 1/8" Shank Mounted Stone
- 2 pc Spanners
- 1 pc Blow Case

636084772054

■ GS-10

10 PIECE GRINDING STONES SET



636084796050

AIR HAMMERS, AIR DRILLS & ACCESSORIES

■ AT-2010/R

150 mm AIR HUMMER WITH 4 PIECE CHISELS

Specifications:

Chisel Shank	0.401"
Blow Per Min.	4500 BPM
Bore Diameter	3/4"
Stroke	1-5/8"
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	3.1 lbs



636084720161

■ AT-4044

1/2" REVERSIBLE AIR DRILL

Specifications:

Free Speed	800 RPM
Chuck Size	1/2"
Spindle Thread	3/8"- 24 UNF
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8"(ID)
Air Consumption @ 90 PSI	8 CFM
Net Weight	2.5 lbs



636084741722

■ AT-2020/R

190 mm AIR HUMMER WITH 4 PIECE CHISELS

Specifications:

Chisel Shank	0.401"
Blow Per Min.	3000 BPM
Bore Diameter	3/4"
Stroke	2-5/8"
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8" (ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	4.2 lbs



636084720659

■ AT-2003/R

4 PIECE AIR CHISEL SET

For use with AT-2010/R,
AT-2020/R and most other air hammer.
Net Weight..... 0.95 lbs



636084720062

■ AT- 4030

3/8" AIR DRILL

Specifications:

Free Speed	1800 RPM
Chuck Size	3/8"
Spindle Thread	3/8"- 24 UNF
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8"(ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	2.5 lbs



636084740022

■ AT-2001

SPRING RETAINER

For use with AT-2010/R,
AT-2020/R and most other air hammer.



636084720000

■ AT-4031

3/8"REVERSIBLE AIR DRILL

Specifications:

Free Speed	1800 RPM
Chuck Size	3/8"
Spindle Thread	3/8"- 24 UNF
Air Inlet	1/4" NPT
Air Pressure	90 PSI
Air Hose	3/8"(ID)
Air Consumption @ 90 PSI	6 CFM
Net Weight	2.5 lbs



636084740107

■ AA-3040

MINI IN-LINE OILER

Specifications:

Air Inlet / Outlet	1/4" NPT
--------------------	----------



636084792250

CUTTING, PUNCH TOOLS & ACCESSORIES

■ AT-6028

3" AIR UTILITY CUT-OFF TOOL



Specifications:

Free Speed.....	18000 RPM
Pad Size.....	3"
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	3 CFM
Net Weight.....	2.7 lbs

636084761010

■ TP-6027B

2 PIECE ALUMNUM OXIDE DISK



For use with AT-6028 Utility Cut-Off Tool. Maximum safe speed 20000 RPM. Size: 3" Dia by 1/16" with 3/8" hole.

636084787256

■ AT-6021

MEDAL SHEAR



Specifications:

Free Speed..... 2500 SPM

Metal Capacity :

Medium Steel.....	1.2mm
Aluminum.....	1.6mm
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	6 CFM
Net Weight.....	3.0 lbs

636084760266

■ AA-3020

AIR BLOW GUN



636084792236

■ AT-6025

AIR NIBBLER(PUSH)



Specifications:

Free Speed..... 3500 RPM

Metal Capacity :

Medium Steel.....	1.6 mm
Aluminum.....	2.0 mm
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	6 CFM
Net Weight.....	2.4 lbs

636084760327

■ AA-3080

ENGINE CLEANING GUN



636084792366

■ AT-6052

AIR PUNCH & FLANGE TOOL



Specifications:

Capacity-Flange.....	1.4 mm
Capacity-Punch.....	1.4 mm
Punch Hole Size.....	5 mm
Air Inlet.....	1/4" NPT
Air Pressure.....	90 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 90 PSI.....	4 CFM
Net Weight.....	2.9 lbs

636084760600

■ AA-20K

20 PIECE PNEUMATIC ACCESSORY KIT

Contains :

- 1 PC Dual Tire Chuck
- 1 PC Tire Gauge
- 1 PC High Pressure Nozzle
- 1 PC Tapered Nozzle
- 1 PC Blow Gun Adapter
- 1 PC Blow Gun
- 2 PC Inflator Needle
- 1 PC 1/4" NPT Female Connectors
- 2 PC 1/4" NPT Male Connectors
- 4 PC 1/4" NPT Male Plug
- 2 PC 1/4" NPT Female Quick Coupler
- 2 PC 1/4" NPT Female Plug
- 1 PC Tape Seal



636084793948

NAILERS & STAPLER

■ AT-3010

18GA., 1-1/4" BRAD NAILER



Specifications:

Fasteners Gauge	18
Fasteners Thickness	0.04"
Fasteners Width	0.05"
Fasteners Length	3/8"-1-1/4"
Air Pressure	60-100 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	3.80 lbs

636084730269

■ AT-3075S

15 GA., 2-1/2" ANGLE FINISH NAILER



Specifications:

Fasteners Gauge	15
Fasteners Length	1-1/4"-2-1/2"
Magazine Capacity	100PCS
Air Pressure	70-110 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	4.84 lbs

636084731419

■ AT-3012

18GA., 2" BRAD NAILER



Specifications:

Fasteners Gauge	18
Fasteners Thickness	0.04"
Fasteners Width	0.05"
Fasteners Length	3/4"-2"
Air Pressure	60-100 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	3.85 lbs

636084730351

■ AT-3090

16 GA., 2-1/2" FULLROUND-HEAD ROOFING COIL NAILER



Specifications:

Fasteners Gauge	11
Fasteners Length	7/8"-1-3/4"
Magazine Capacity	120PCS
Air Pressure	70-100 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	4.5 lbs

636084731389

■ AT-3030

18GA., 1-1/2" NARROW CROWN STAPLER



Specifications:

Fasteners Gauge	18
Fasteners Thickness	0.04"
Fasteners Width	0.05"
Fasteners Length	5/8"-1-1/2"
Magazine Capacity	100 PCS
Air Pressure	60-100 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	3.55 lbs

636084730542

■ AT-3095PA

34' CLIPPED HEAD FRAMING NAILER



Specifications:

Fasteners Shank	0.113"-0.131"
Fasteners Length	2"-3-1/2"
Magazine Capacity	78-90 PCS
Air Pressure	70-110 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	8.4 lbs

636084731390

■ AT-3070

16 GA., 2-1/2" FINISH NAILER



Specifications:

Fasteners Gauge	16
Fasteners Length	3/4"-2-1/2"
Magazine Capacity	100PCS
Air Pressure	60-100 PSI
Air Hose	3/8"(ID)
Air Inlet	1/4 NPT
Net Weight	4.1 lbs

636084730955

SPRAY GUNS & ACCESSORIES

■ AS-1020

LOW PRESSURE SPRAY GUN



Specifications:

Canister.....	800 cc
Air Inlet.....	1/4" NPS
Air Pressure.....	30 - 45 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 45 PSI.....	6 CFM
Net Weight.....	1.41 lbs

636084781186

■ AS-1005

HVLP GRAVITY AIR SPRAY GUN



Specifications:

Nozzle Size.....	1.5 mm
Canister.....	600 cc
Air Inlet.....	1/4" NPS
Air Pressure.....	35 - 43 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 43 PSI.....	8 CFM
Net Weight.....	1.62 lbs

636084781087

■ AS-1050

HIGH PRESSURE SPRAY GUN



Specifications:

Nozzle Size.....	1.8 mm
Canister.....	1000 cc
Air Inlet.....	1/4" NPS
Air Pressure.....	50 - 60 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 60 PSI.....	8 CFM
Net Weight.....	2.4 lbs

636084781353

■ AB-1003

PROFESSIONAL AIR BRUSH KIT



Specifications:

Cup Capacity.....	7 cc
Nozzle Size.....	0.3 mm
Control.....	Push-Button
Air Inlet.....	1/8" NPS
Air Pressure.....	20-40 PSI
Air Hose.....	3/16" (ID)
Air Consumption.....	1 CFM

636084780028

■ AS-1001

GRAVITY AIR SPRAY GUN



Specifications:

Nozzle Size.....	0.8 mm
Canister.....	250 cc
Air Inlet.....	1/4" NPS
Air Pressure.....	43 PSI
Air Hose.....	3/4" (ID)
Air Consumption @ 50 PSI.....	4 CFM
Net Weight.....	0.66 lbs

636084781018

■ AA-2002

WATER & OIL SEPARATOR



Specifications:

Air Inlet / Outlet.....	1/4" NPT
-------------------------	----------

636084791543

■ AS-1002

GRAVITY AIR SPRAY GUN



Specifications:

Nozzle Size.....	1.4 mm
Canister.....	600 cc
Air Inlet.....	1/4" NPS
Air Pressure.....	50-60 PSI
Air Hose.....	3/8" (ID)
Air Consumption @ 60 PSI.....	8 CFM
Net Weight.....	1.62 lbs

636084781032

FILTER, REGULATOR & LUBRICATOR

AA-2121F



636084793622

1/4" FILTER

Specifications:

Filter Element	20 μ
Max. Pressure	145 PSI
Max. Flow	35 CFM
Ambient Temp	5-60°C
Drain Capacity	15 ml

2408008LNGI



636084303616

AIR REGULATOR & GAUGE

Specifications:

Air Inlet / Outlet	1/4" NPT
Max. Work Pressure	150 PSI

AA-2023F AA-2024F



636084793486
636084793530

AA-2023F : 3/8" FILTER

Specifications:

Filter Element	20 μ
Max. Pressure	145 PSI
Max. Flow	69 CFM
Ambient Temp	5-60°C
Drain Capacity	80 ml

AA-2024F : 1/2" FILTER

Specifications:

Filter Element	20 μ
Max. Pressure	145 PSI
Max. Flow	69 CFM
Ambient Temp	5-60°C
Drain Capacity	80 ml

AA-2023FR AA-2024FR



636084793493
636084793547

AA-2023FR : 3/8" FILTER & REGULATOR

Specifications:

Max. Pressure	175 PSI
Ambient Temp	5-60°C
Drain Capacity	80 ml

AA-2024FR : 1/2" FILTER & REGULATOR

Specifications:

Max. Pressure	175 PSI
Ambient Temp	5-60°C
Drain Capacity	80 ml

AA-2121R AA-2123R AA-2124R



636084793653
636084793660
636084793677

1/4" AIR REGULATOR & GAUGE

Specifications:

Max. Pressure	145 PSI
Ambient Temp	5-60°C
Gauge Port	1/8" NPT

3/8" AIR REGULATOR & GAUGE

Specifications:

Max. Pressure	175 PSI
Ambient Temp	5-60°C
Gauge Port	1/4" NPT

1/2" AIR REGULATOR & GAUGE

Specifications:

Max. Pressure	135 PSI
Ambient Temp	5-60°C
Gauge Port	1/4" NPT

AA-2022L AA-2023L AA-2024L



636084793455
636084793509
636084793554

AA-2022L : 1/4" LUBRICATOR

Specifications:

Max. Pressure	145 PSI
Max. Flow	62 CFM
Ambient Temp	5-60°C
Oil Capacity	125 ml
Usable Oil	ISO VG-32

AA-2023L : 3/8" LUBRICATOR

Specifications:

Max. Pressure	175 PSI
Max. Flow	69 CFM
Ambient Temp	5-60°C
Oil Capacity	125 ml
Usable Oil	ISO VG-32

AA-2121FR



636084793639

1/4" FILTER & REGULATOR

Specifications:

Filter Element	20 μ
Max. Pressure	145 PSI
Max. Flow	35 CFM
Ambient Temp	5-60°C
Drain Capacity	15 ml

AA-2024L : 1/2" LUBRICATOR

Specifications:

Max. Pressure	175 PSI
Max. Flow	77 CFM
Ambient Temp	5-60°C
Oil Capacity	125 ml
Usable Oil	ISO VG-32

ACCESSORIES

309ASS 309ASM



636084715921
636084713002

309ASS :
9 PIECE
3/8" IMPACT SOCKETS

SAE Size:
5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16",
3/4"

309ASM :
9 PIECE
3/8" IMPACT SOCKETS

Metric Size:
8, 10, 11, 12, 13, 14, 17, 19

609ASSB 609ASMB



636084715983
636084715976

609ASSB :
9 PIECE
3/4" IMPACT SOCKETS

SAE Size:
3/4", 13/16", 7/8", 15/16", 1", 1-1/16",
1-1/8", 1-1/4"

609ASMB :
9 PIECE
3/4" IMPACT SOCKETS

Metric Size:
19, 21, 22, 24, 26, 27, 29, 32

309ADS 309ADM



636084715945
636084715938

309ADS :
9 PIECE
3/8" DEEP IMPACT SOCKETS

SAE Size:
5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16",
3/4"

309ADM :
9 PIECE
3/8" DEEP IMPACT SOCKETS

Metric Size:
8, 10, 11, 12, 13, 14, 17, 19

609ADSA 609ADMA



636084716003
636084715990

609ADSA :
9 PIECE
3/4" DEEP IMPACT SOCKETS

SAE Size:
1", 1-1/16", 1-1/8", 1-1/4", 1-5/16, 1-3/8",
1-7/16", 1-1/2"

609ADMA :
9 PIECE
3/4" DEEP IMPACT SOCKETS

Metric Size:
26, 27, 29, 30, 32, 35, 36, 38

411ASS 411ASM



636084713088
636084713071

411ASS :
11 PIECE
1/2" IMPACT SOCKETS

SAE Size:
7/16", 1/2", 9/16", 11/16", 3/4", 13/16",
8/7", 15/16", 1"

411ASM :
11 PIECE
1/2" IMPACT SOCKETS

Metric Size:
10, 11, 12, 13, 14, 17, 19, 21, 22, 24

806ASS 806ASM



636084716027
636084716010

806ASS :
6 PIECE 1" IMPACT SOCKETS

SAE Size:
1-1/4", 1-3/8", 1-7/16", 1-1/2", 1-5/8"

806ASM :
6 PIECE 1" IMPACT SOCKETS

Metric Size:
32, 35, 36, 38, 41

412ADS 412ADM



636084715969
636084715952

412ADS :
12 PIECE
1/2" DEEP IMPACT SOCKETS

SAE Size:
3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4",
13/16", 8/7", 15/16", 1"

412ADM :
12 PIECE
1/2" DEEP IMPACT SOCKETS

Metric Size:
10, 12, 13, 14, 16, 17, 19, 21, 22, 24

808ADS



636084713187

808ADS :
8 PIECE
1" DEEPIMPACT SOCKETS

SAE Size:
13/16", 15/16", 1", 1-1/16", 1-1/8", 1-1/4", 1-1/2"

AA-1301



636084793684

2-1/2' WHIP HOSE WITH SWIVEL CONNECTOR

Specifications:

Air Inlet _____ 1/4" NPT
 Work Pressure _____ 200 PSI
 Length _____ 2.5'

AA-1302



636084793790

5' WHIP HOSE WITH SWIVEL CONNECTOR

Specifications:

Air Inlet _____ 1/4" NPT
 Work Pressure _____ 200PSI
 Length _____ 5'

AA-3061



636084793714

DUAL FOOT AIR CHUCK

AA-1012 AA-1014



636084791161
 636084791202

1/4" NYLON RECOIL AIR HOSE

Specifications:

Air Inlet _____ 1/4" NPT
 Work Pressure _____ 200 PSI
 Length _____ 25'

3/8" NYLON RECOIL AIR HOSE

Specifications:

Air Inlet _____ 3/8" NPT
 Work Pressure _____ 200 PSI
 Length _____ 25'

AA-3060



636084792267

TIRE CHUCK

AA-1061 AA-1062 AA-1064



636084793752
 636084793769
 636084793783

1/4" PU BRAID AIR HOSE WITH SWIVEL FITTING & GRIP

Specifications:

Work Pressure _____ 210 PSI
 Length _____ 25'
 Net Weight _____ 1.1 LB

Specifications:

Work Pressure _____ 210 PSI
 Length _____ 50'
 Net Weight _____ 2.3 LB

Specifications:

Work Pressure _____ 210 PSI
 Length _____ 100'
 Net Weight _____ 4.1 LB

AA-6001A



636084792908

TIRE INFLATOR WITH GAUGE

AA-1706



636084793707

3/8" AIR HOSE REPAIR KIT

Contains:

2 PC Hose Clamp
 1 PC 3/8" I.D. Solid Hose Mender
 1 PC 3/8" I.D. x 1/4" NPT Solid Hose Mender

AA-1705



636084793691

AIR INFLATOR KIT

Contains:

1 PC Tapered Brass Nozzle
 1 PC Inflator Needle
 1 PC Chuck Adapter
 1 PC Inflator Tube
 1 PC Screw-On Chuck

- MS-1/4F
- MS-3/8F



MS-1/4F :
QUICK COUPLER
1/4" NPT FEMALE

MS-3/8F :
QUICK COUPLER
3/8" NPT FEMALE

636084701696
636084701610

- GMS-1/4F
- GMS-3/8F
- GMS-1/2F



GMS-1/4F :
LARGE FLOW QUICK COUPLER
1/4" NPT FEMALE

GMS-3/8F :
LARGE FLOW QUICK COUPLER
3/8" NPT FEMALE

GMS-1/2F :
LARGE FLOW QUICK COUPLER
1/2" NPT FEMALE

636084702976
636084702952
636084702938

- MS-1/4M
- MS-3/8M



MS-1/4M :
QUICK COUPLER
1/4" NPT MALE

MS-3/8M :
QUICK COUPLER
3/8" NPT MALE

636084701757
636084701771

- GMS-1/4M
- GMS-3/8M
- GMS-1/2M



GMS-1/4M :
LARGE FLOW QUICK COUPLER
1/4" NPT MALE

GMS-3/8M :
LARGE FLOW QUICK COUPLER
3/8" NPT MALE

GMS-1/2M :
LARGE FLOW QUICK COUPLER
1/2" NPT MALE

636084702983
636084702969
636084702945

- MP-1/4F
- MP-3/8F



MP-1/4F :
QUICK PLUG
1/4" NPT FEMALE

MP-3/8F :
QUICK PLUG
3/8" NPT FEMALE

636084701559
636084701610

- GMP-1/4F
- GMP-3/8F
- GMP-1/2F



GMP-1/4F :
LARGE FLOW QUICK PLUG
1/4" NPT FEMALE

GMP-3/8F :
LARGE FLOW QUICK PLUG
3/8" NPT FEMALE

GMP-1/2F :
LARGE FLOW QUICK PLUG
1/2" NPT FEMALE

636084702914
636084702891
636084702877

- MP-1/4M
- MP-3/8M



MP-1/4M :
QUICK PLUG
1/4" NPT MALE

MP-3/8M :
QUICK PLUG
3/8" NPT MALE

636084701597
636084701658

- GMP-1/4M
- GMP-3/8M
- GMP-1/2M



GMP-1/4M :
LARGE FLOW QUICK PLUG
1/4" NPT MALE

GMP-3/8M :
LARGE FLOW QUICK PLUG
3/8" NPT MALE

GMP-1/2M :
LARGE FLOW QUICK PLUG
1/2" NPT MALE

636084702821
636084702907
636084702884

- 2N11-02N02N
- 2N11-03N03N
- 2N11-04N04N



636084301919
636084301964
636084301971

2N11-02N02N :
1/4" NPT FEMALE
CONNECTOR

2N11-03N03N :
3/8" NPT FEMALE
CONNECTOR

2N11-04N04N :
1/2" NPT FEMALE
CONNECTOR

- 2406010
- 2406033
- 2406016
- 84006010



636084303449
636084303456
636084304118
636084304132

PRESSURE RELIEF VALVE

2406010 :
Size..... 1/4" NPT
Relief Pressure..... 100 PSI

2406033 :
Size..... 1/4" NPT
Relief Pressure..... 125 PSI

2406016 :
Size..... 1/4" NPT
Relief Pressure..... 150 PSI

84006010 :
Size..... 1/4" NPT
Relief Pressure..... 200 PSI

- 2N01-02N02N030C
- 2N01-03N03N030C
- 2N01-04N04N030C



636084301926
636084301933
636084301988

2N01-02N02N030C :
1/4" NPT MALE CONNECTOR

2N01-03N03N030C :
3/8" NPT MALE CONNECTOR

2N01-04N04N030C :
1/2" NPT MALE CONNECTOR

- 2140009



636084300387

CANISTER AIR FILTER

Specifications:
Size..... 1" NPT
Metal With Filter Element

- 2N02-02N03NC
- 2N02-02N04NC
- 2N02-03N04NC



636084301940
636084301995
636084302008

2N02-02N03NC :
1/4" NPT Male x 3/8" NPT
Female ADAPTER

2N02-02N04NC :
1/4" NPT Male x 1/2" NPT
Female ADAPTER

2N02-03N04NC :
3/8" NPT Male x 1/2" NPT
Female ADAPTER

- 2140019A
- 2140020A



636084300431
636084300448

2140019A :
1/2" CANISTER AIR FILTER

2140020A :
3/4" CANISTER AIR FILTER

- 2N02-03N02NC
- 2N02-04N02NC
- 2N02-04N03NC



636084301957
636084302015
636084302022

2N02-03N02NC :
3/8" NPT Male x 1/4" NPT
Female ADAPTER

2N02-04N02NC :
1/2" NPT Male x 1/4" NPT
Female ADAPTER

2N02-04N03NC :
1/2" NPT Male x 3/8" NPT
Female ADAPTER

- 2142002
- 2142013



636084300110
636084300158

AIR FILTER ELEMENT

2142002:
Specifications:
Diameter..... 3.743"
Height..... 2.383"

2142013:
Specifications:
Diameter..... 2.561"
Height..... 1.871"

ACCESSORIES

■ 2414025



1/2" CHECK VALVE

636084300769

■ CV1212M
■ CV3434M



CHECK VALVE

CV1212M

Internal Diameter _____ 1/2"

CV3434M

Internal Diameter _____ 3/4"

636084300776

636084300783

■ 2405011

1/4" PT DRAIN VALVE



636084303913

■ 2407003
■ 2407005
■ 2407007
■ 2407008

UNLOADING VALVE

2407003 :

Internal Diameter _____ 1/4" NPT

Work Pressure _____ 95-125 PSI

2407005 :

Internal Diameter _____ 1/4" NPT

Work Pressure _____ 140-175 PSI

2407007 :

Internal Diameter _____ 1/4" NPT

Work Pressure _____ 105-135 PSI

2407008 :

Internal Diameter _____ 1/4" NPT

Work Pressure _____ 120-150 PSI



636084301049

636084901034

636084304613

636084901058

■ 2413020N
■ 2413012N
■ 2413002N

2413020N :

1/4" NPT BALL VALVE

2413012N :

3/8" NPT BALL VALVE

2413002N :

1/2" NPT BALL VALVE



636084303418

636084303425

636084303432

■ 059-404010

VIBRATION DAMPER

Size _____ 4" x 4" x 1"



636084304811

■ 2E21-025T

■ 2E21-013TB

2E21-025T :

Pressure Switch _____ 95-125 PSI

Four Port With ON/OFF Switch

2E21-013TB :

Pressure Switch _____ 95-125 PSI

Single Port With ON/OFF Switch



636084301025

636084301032

■ 2E21-008X

■ 2E21-042T

2E21-008X :

Pressure Switch _____ 140-175 PSI

Single Port With ON/OFF Switch

2E21-042T :

Pressure Switch _____ 140-175 PSI

Four Port With ON/OFF Switch



636084301049

636084301056

■ 2E21-008XN

■ 2E21-035TN

2E21-008XN :

Pressure Switch _____ 140-175 PSI

Single Port With Metal Box

1/4" NPT Female

2E21-035TN :

Pressure Switch _____ 105-135 PSI

Single Port With Metal Box

1/4" NPT Male



636084301063

636084301049

AA-4032

5 PIECE BRASS COUPLER

Contains :

- 1 PC Female Quick Coupler
- 2 PC Male Connectors
- 1 PC Female Connectors
- 1 PC Male Hose Connector



636084792472

MQC-2B

2 WAY QUICK COUPLER

Specifications:

- Air Inlet / Outlet 1/4" NPT
- Max. Work Pressure 200 PSI



636084701801

MQC-3B

3 WAY QUICK COUPLER

Specifications:

- Air Inlet / Outlet 1/4" NPT
- Max. Work Pressure 200 PSI



636084701825

2416101

CARRY TANK MANIFOLD

Specifications:

- Size 1/2" NPT
- Relief Pressure 150 PSI



636084304415

2D12-15D200I

2D12-20D200I

2D12-15D200I :

1-1/2" PRESSURE GAUGE

- Thread Size 1/8" NPT
- Range 200 PSI



636084301230

636084301247

2D12-20D200I :

2" PRESSURE GAUGE

- Thread Size 1/4" NPT
- Range 200 PSI

2D12-15V200I

2D12-15V200I2

2D12-20V200I

2D12-15V200I :

1-1/2" PRESSURE GAUGE

- Thread Size 1/8" NPT
- Range 200 PSI



636084301254

636084301261

636084301278

2D12-15V200I2 :

1-1/2" PRESSURE GAUGE

- Thread Size 1/4" NPT
- Range 200 PSI

2D12-20V200I :

2" PRESSURE GAUGE

- Thread Size 1/4" NPT
- Range 200 PSI

2409003

COLD START/OUTLET VALVE



636084781186

CV-1

CV-2

LOAD GENIE

CV-1

- Pressure 95-125 PSI

CV-2

- Pressure 145-175 PSI



636084303920

636084303937



PUMA INDUSTRIES, INC.

1992 Airways BL, Memphis, TN 38114
TEL:1-901-744-7979 FAX:1-901-744-7579
E-mail:sales@pumaaircenter.com
URL:<http://www.pumaairusa.com>



* These products are protected by one or more patents. Others may be pending.
* All products functions may re-design or be changed without notice.