

- Oil lubricated, two stage cast iron pumps. Two cylinder V type or Three cylinder radial type pumps.
- 1/2" outlet ball valve and 1/4" extended drain ball valve on all units.
- All tanks are rated at 200 PSI with either ASME or CRN certified.
- Professional grade units are available in accessories such as automatic water drain, vibration damper, and high flow heavy duty regulator filter.



Model		TE-3040V	TE-5040V	TE-6540V
Electric Motor	H.P.	3	5	6.5
	R.P.M / Frame	3450 / 56	3450 / 56	3450 / 182
	Volt./ Phase/ Amp.	208-230 / Single / 16.6-15	208-230 / Single / 23-21	208-230 / Single / 24.5-23
Pump R.P.M		985	985	1268
Max. Working PSI.		175	175	175
FAD-CFM	@ 90 PSI	10.2	14	17
	@ 175 PSI	9.3	12.8	16
TANK	Gal.	40	40	40
	Style	Vertical	Vertical	Vertical
	Code	ASME	ASME	ASME
Weight (Lbs)		260	280	295
Magnetic Starter		n/a	Option	Combo Pressure Switch Starter



Model		TE-5080V	TE-6580V	TN-6580VM
Electric Motor	H.P.	5	6.5	6.5
	R.P.M / Frame	3450 / 56	3450 / 182	3450 / 182
	Volt./ Phase/ Amp.	208-230 / Single / 21-19	208-230 / Single / 24.5-23	208-230 / Single / 24.5-23
Pump R.P.M		985	1268	985
Max. Working PSI.		175	175	175
FAD-CFM	@ 90 PSI	14	17	17
	@ 175 PSI	12.8	16	16
TANK	Gal.	80	80	80
	Style	Vertical	Vertical	Vertical
	Code	ASME / CRN	ASME / CRN	ASME / CRN
Weight (Lbs)		460	475	500
Magnetic Starter		Option	Combo Pressure Switch Starter	Yes

