



QC CL-7000 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 1147 Watts / Low: 794 Watts	
Air Flow	Hi: 6924 CFM / Low: 5518 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	5300 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 3470 SQ FT	
# of Speeds	2	
Duct Diameter	24"	
Duct Length	9 feet	
Motor Head Diameter	24 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Not Included)	Recommended 8 Hour Electronic Timer (IT-30070) and	
	HI-LOW-OFF Switch (IT-35000)	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	9.24 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	108 lbs.	
Box Dimensions	41" x 28" x 39"	
In The Box	-QC CL-7000 Motorhead	-Damper Box
	-Ceiling Grille	-9 Foot Duct
	-Cut-out Template	-Accessory Bag
	-Window Locks	

