

RESIDENTIAL AND COMMERCIAL



EASE OF INSTALLATION AND SERVICEABILITY

- Compact Design to Save Space
- Wi-Fi Technology for Remote Monitoring, Management and Recirculation Control.
- Simple Gas Conversion
- Includes Certified Isolation Valves for Potable Water

OPTIONAL ACCESSORIES

Condensate Neutralizer, ScaleCutter, Additional Controllers, Pipe Cover, EZConnect™ Cables, control-r™ Wi-Fi Module, External Recirculation Pump, Wireless Accessories, and many more.

Visit rinnai.us for a complete list of accessories.

HIGH-EFFICIENCY (NON-CONDENSING) TANKLESS WATER HEATER

Installation Type	Internal (Indoor) Residential and Commercial Applications; Certified for installation in Manufactured (Mobile) Homes	
Model Number	RL94i (REU-VC2537FFUD-US)	
Approved Gas Types	Natural and Propane	
High Altitude Approved	Up to 10,200 ft. (3,109 m)	
Water Flow Control	Water Flow Sensor, Electronic Water Control and Fixed Bypass Control	
Efficiency		UEF: 0.81
	Ratings not certified by AHRI	EF: 0.82
Controller	Included: MC-91-2US Optional: MC-100V-1US (Deluxe), BC-100V-1US (Bathroom), MCC-91-2US (Hydronic and Commercial Applications), MC-195T-US (for use with Circ-Logic), control-r™ Wi-Fi Module	
Certifications	AHRI, ANSI Z21.10.3, and CSA 4.3	

Warranty

- Heat Exchanger: 12 years* for residential
 - All Other Parts and Components: 5 Years*
 - Reasonable Labor: 1 Year
- * 3 years if used as a circulation water heater within a circulation loop when the water heater is in series with a circulation system and all circulating water flows through the water heater, and where an aquastat/thermostat, timer, or an on-demand recirculation system is not incorporated. Refer to the Tankless Water Heater Installation and Operation manual for complete warranty information.

Safety Devices

Flame Failure - Flame Rod, Boiling Protection, Combustion Fan RPM Check, Over Current - Glass Fuse, Remaining Flame (OHS), Thermal Fuse and Automatic Frost Protection

Included with Purchase

Tankless Water Heater, Color Coded Cold (Blue) and Hot (Red) Isolation Valves, Pressure Relief Valve, MC-91-2 Temperature Controller

Additional Features

- Complies with South Coast Air Quality Management District 40 ng/J or 55 ppm NOx Emission Levels
- 1/2 in. (13 mm) Gas Line Compatible
- Wi-Fi & Recirculation Capable



CERTIFIED TO ANSI Z21.10.3 — CSA 4.3

TECHNICAL SPECIFICATIONS


SPECIFICATION		RL94i
Dimensions - w, h, d		14.04 in. x 22.95 in. x 9.27 in. (356.6 mm x 583 mm x 235.5 mm)
Minimum Gas Consumption Btu/h		10,300
Maximum Gas Consumption Btu/h		199,000
Flow Rate ¹ (Min - Max)		0.26 - 9.8 GPM (1.0 - 37.1 L/min)
Weight		46.3 lbs. (21.0 kg.)
Sound Level		47 dB
Electrical	Normal	97 W
	Standby	2 W
	Freeze Protection	120 W
	Max With Pump	8 Amps
	Max Without Pump	4 Amps
	Fuse	10 Amps
Temperature (with remote)		98° - 120° F (37°C - 49°C) (factory default) 98° - 185° F (37° - 85° C) available with the MCC-91-2 controller for commercial and hydronic applications
Temperature (without remote)		120° F (49°C) (factory default) and 140° F (60°C)
Gas Supply Pressure ²		- Natural: 4 in. w.c. - 10.5 in. w.c. (2.5 mbar - 26.1 mbar) - Propane: 8 in. w.c. - 13.5 in. w.c. (20 mbar - 33.6 mbar)
Ignition System		Direct Electronic Ignition
Electronic Connections		- Appliance: AC 120 Volts, 60Hz. - Temperature Controller: DC 12 Volts (Digital)
Water Supply Pressure		- Minimum: 20 PSI (Recommended 30-80 PSI for max performance) - Maximum: 150 PSI
Controller Cable		Non-Polarized Two Core Cable (Minimum 22 AWG)
Service Connections		- Gas Supply: 3/4 in. (19 mm) NPT - Cold Water Inlet: 3/4 in. (19 mm) NPT - Hot Water Outlet: 3/4 in. (19 mm) NPT
Clearances from Combustibles		- Top: 6 in. (152 mm) - Bottom/Ground: 12 in. (305 mm) - Front: 6 in. (152 mm)* - Back: 0 in. - Sides: 2 in. (51 mm) - Vent: 0 in.
Clearances from Non-Combustibles		- Top: 2 in. (51 mm) - Bottom/Ground: 12 in. (305 mm) - Front: 6 in. (152 mm)* - Back: 0 in. - Sides: 1/2 in. (13 mm) - Vent: 0 in.

* Clearance for servicing is 24 in. (610 mm) in front of water heater

¹ Minimum flow may vary slightly depending on the temperature setting and the inlet water temperature. Minimum activation flow is 0.4 GPM (1.5 L/min).

² The maximum gas supply pressure must not exceed the value specified by the manufacturer.


WATER FLOW CURVE




DIMENSIONS

in. (mm)


FRONT



SIDE



BOTTOM



DIMENSION	Inches (mm)	DIMENSION	Inches (mm)
A (GAS)	1.31 (33.2)	D	4.33 (110)
A (COLD)	1.93 (49)	E	2.89 (73.3)
A (HOT)	1.35 (34.4)	F	1.85 (47)
B	4.21 (106.9)	G	3.44 (87.3)
C	1.17 (29.8)		