

5 HP and 7½ HP Two-Stage, Medium-Duty 175 PSI Performance Series Air Compressors



SA2560V

Solid steel base with bolt-down claw feet



5 HP and 7½ HP Two-Stage, Medium-Duty 175 PSI Performance Series Air Compressors



Specifications

Model #	Motor						Pump				Tank		Dimensions	
	НР	Volt.	Phase	Amp Draw	Breaker Size	Wire Size*	Cyl.	RPM	Disp. CFM	SCFM @175 PSI	Size (Gallons)	Config.	L x W x H (inches)	Ship Wt. (lbs)
SA2560V	5	230	1	19.6	30A	10	2	1300	19.5	13.5	60	٧	35 x 20 x 71	340
SA2580V	5	230	1	19.6	30A	10	2	1300	19.5	13.5	80	V	37 x 24 x 73	435
SA27580V	7.5	230	1	32	50A	10	2	1065	24.5	17	80	V	37 x 24 x 73	515

^{*}Minimum wire size required if less than 50' from power source breaker box.

Parts & Accessories

Model #	Auto Electric Tank Drain	Install Kit	Vibration Pads Only	Drive Belt (1)	Oil (capacity)	Pressure Switch	Pressure Gauge	Refrigerated Air Dryer 140°	Refrigerated Air Dryer 250°
SA2560V	907001	824678	824679	829003	826020**(1.1 qt.)	82779	82516	SRD0025	SRD0220
SA2580V	907001	824678	824679	829003	826020**(1.1 qt.)	82779	82516	SRD0025	SRD0220
SA27580V	907001	824678	824679	829018	826020**(1.7 qt.)	82779	82516	SRD0025	SRD0220

^{**}Oil sold in 1 quart bottles.



Specifications subject to change without notice. Units may not be exactly as pictured.