

SPECIFICATIONS

	Description
Engine	14.5HP (603 CC) Kawasaki
Engine Specifications	See engine Manual for Specifications
Starting	Electric Start
Battery	12 Volt ("U1" recommended), 340CCA
Fuel	2.5 Gal. (9.46 L), Unleaded Gasoline (MIN 87 Octane) MAX 10% Ethanol
Overall Dimesions	139.5" L x 47" W x 34" H (MAX)
Console Cable Length	10' 4"
Offset Distance (Tow ball to offset cutting edge)	Max 52", Mid 39" (See page 19 for details)
Offset Positions	5 (2 Left, 1 Center, 2 Right)
Cutting Height	3" - 7.5"
Cutting Width	44"
Blade Style	Swing Blade w/ Stump Jumper
Discharge	Rear
Drive System	Belt
Blade Engagement	Electric Clutch
Towing Speed	5 MPH MAX
Mowing Speed	5 MPH (Flat Ground) 4 MPH MAX (Rough Ground)
Unit Dry Weight	640 Lbs. (290 kg)
Tire PSI	20 PSI Recommended (MIN 15 PSI - MAX 35 PSI)
Quick Reference - Maintenance Parts	
Description	Part Number
Belt - B X 56"	20937
Wheel/Tire - 16/650X8	21262
Bearing - Blade; RT44	4845
Blade - Off-Set, Rough Cut	10358

Note:

- For other part numbers, refer to the Parts Diagrams on pages 22-30.

