



# TIMECUTTER®

SW SERIES ZERO TURN TRACTORS

## PREMIUM SEATS

18" (46 cm) extra tall seats for increased comfort

## INTUITIVE STEERING WHEEL

An adjustable column make these zero turn tractors a great choice and easy to get on and off of.

## VERSATILITY

TimeCutter comes standard with a hitch for pulling a variety of Brinly attachments.

AWARD  
WINNING  
FEATURE!\*

## SMART PARK™ BRAKING SYSTEM

Toro's unique braking system automatically stops the mower deck and sets the parking brake when you need to get off the mower while keeping the engine running, for added convenience and ease of use.



*"This mower is great! Very easy to use, cuts well, especially when mowing on a hill."*

DTun via Toro.com | Albany, NY





TIMECUTTER® SW	SW3200 74780	SW4200 74784	SW5000 74790	SWX5000 74795	SWX5050 74797
ENGINE* AT 3600 RPM	Toro® 452cc	» 24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Box
ENGINE GUARD	Standard	Standard	Standard	Standard	Standard
FUEL CAPACITY	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)
MOWING DECK	32" (81 cm) – 13 ga. 1 blade	» 42" (107 cm) – 13 ga. 2 blades	» 50" (127 cm) – 12 ga. 3 blades	» 50" (127 cm) – 10 ga. fabricated 3 blades	50" (127 cm) – 10 ga. fabricated 3 blades
BLADE TIP SPEED	18,959 ft/min (5,779 m/min)	17,810 ft/min (5,428 m/min)	» 18,330 ft/min (5,587 m/min)	18,330 ft/min (5,587 m/min)	18,330 ft/min (5,587 m/min)
DECK WASHOUT PORTS	Standard	Standard	Standard	Standard	Standard
HEIGHT OF CUT	1.5" – 4.5" (3.8 – 11.4 cm)	1.5" – 4.5" (3.8 – 11.4 cm)	1.5" – 4.5" (3.8 – 11.4 cm)	1.5" – 4.5" (3.8 – 11.4 cm)	1.5" – 4.5" (3.8 – 11.4 cm)
FRAME	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge	Heavy Duty 10 Gauge
HITCH	Standard	Standard	Standard	Standard	Standard
TRANSMISSIONS	Dual Hydrostatic	Dual Hydrostatic	Dual Hydrostatic	Dual Hydrostatic	» HG-ZT2800
SMART PARK™ BRAKING SYSTEM	Standard	Standard	Standard	Standard	Standard
TIRES (REAR)	18" x 6.0" (45.7 cm x 15.2 cm)	» 18" x 7.5" (45.7 cm x 19.1 cm)	» 18" x 9.5" (45.7 cm x 24.1 cm)	18" x 9.5" (45.7 cm x 24.1 cm)	» 20" x 10" (50.8 cm x 25.4 cm)
TIRES (FRONT)	11" x 4" (27.9 cm x 10.2 cm)	» 13" x 5" (33 cm x 12.7 cm)	13" x 5" (33 cm x 12.7 cm)	13" x 5" (33 cm x 12.7 cm)	13" x 5" (33 cm x 12.7 cm)
SEAT	18" (46 cm) Extra-Tall	18" (46 cm) Extra-Tall	» 18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium
ARMRESTS	Optional	Optional	Optional	Optional	» Standard
HOURLY METER	Optional	Optional	Optional	Optional	» Standard
FLOOR MAT	Optional	Optional	Optional	Optional	Optional
STORAGE DIMENSIONS (W x L x H)	36.2" x 78.9" x 45.4" (92 x 200.4 x 115.3 cm)	45.3" x 78.9" x 45.4" (115 x 200.4 x 115.3 cm)	54.6" x 78.9" x 45.4" (138.7 x 200.4 x 115.3 cm)	53.5" x 78.9" x 45.9" (135.9 x 200.4 x 116.6 cm)	53.5" x 78.9" x 45.9" (135.9 x 200.4 x 116.6 cm)
RESIDENTIAL LIMITED WARRANTY**	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours

» = Enhanced or Step-up feature



### TORO COMMERCIAL V-TWIN ENGINE

Features a patent pending self-cleaning air filter housing and a two-barrel carburetor for maximum performance.



### KEY CHOICE

Remove the key to prevent others from mowing in reverse for added piece of mind.



### LESS MOWING TIME = LONGER MOWING LIFE

TimeCutter owners report an average time savings of 45% vs. their previous mower.†



### PROFESSIONAL QUALITY OF CUT

Toro is counted on to maintain premier grounds such as the Super Bowl® fields, NASCAR® speedways, and the best golf courses in the world.



### 3 YEAR UNLIMITED HOUR WARRANTY\*\*

Warrantied against defects in materials and workmanship for 3 years with no hour restrictions. See your Toro dealer for details.

**TORO**

490-9655 ©2017 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \*The gross or net horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. \*\*See retailer for warranty details. †Time savings from 2008 – 2012 survey results for Toro residential zero-turn mowers, as reported by owners. ▲2015 Pro Tool Innovation Award Winner