
Document No:	125-7599		Rev	: C		Issue Date	: 1/18/2	2016	Page	1 of 8
Title:	SDS-FUEL CONDITIONER o						Originato	or:	Erdman	
Confidential Property of TORO Bloomington, Minnesota		Approx Weight:			0.001	lb	Originating Location:			LYNDALE
		Sin	nilar To:					Supe	rsedes:	
Release/Change Authorization Number: ECM 5111065 UPDATE SDS ATTACHMENT										

Material Safety Data Sheet

SEE ADDITIONAL PAGES





Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Toro, Inc 8111 Lyndale Ave S Bloomington, MN 55420-1196 Tel: 1-888-384-9939

Product Trade Name: Toro Premium Fuel Treatment

CAS Number: Mixture Synonyms/Other: N/A

Recommended Use: Fuel Additive
Restrictions on Use: Not determined
Created Date: 4/29/2015
Preparation/Revision Date: 4/29/2015

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

SDS CODE: 13315

SECTION 2

HAZARD IDENTIFICATION

Appearance: Clear, colorless to light yellow fluid.

Odor: Mild, solvent odor.

Classification: Skin corrosion / irritation category 2

Sensitization - skin category 1 Eye damage / irritation category 2 Aspiration toxicant category 2

Hazardous to the aquatic environment (acute hazard) category 3 Hazardous to the aquatic environment (chronic hazard) category 3

Flammable liquid category 4

Target Organs: Skin, Eyes, Stomach and intestines

Pictogram(s):

Signal Word: WARNING

Hazard Statement: H227 - Combustible liquid

 $\ensuremath{\mathsf{H305}}$ - $\ensuremath{\mathsf{May}}$ be harmful if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects

Other Hazards: Not determined.

Prevention: P210 - Keep away from heat/sparks/open flames/hot surfaces - No smoking

P261 - Avoid breathing fume/gas/mist/vapours/spray

P264 - Wash hands thoroughly after handling

P272 - Contaminated work clothing should not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P285 - In case of inadequate ventilation wear respiratory protection



Safety Data Sheet Toro Premium Fuel Treatment Revision Date: 4/29/15

Response: P321 - Specific treatment (see Section 4)

P331 - Do NOT induce vomiting

P362 - Take off contaminated clothing and wash before reuse

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352 - IF ON SKIN: Wash with soap and water

P333+P313 - If skin irritation or a rash occurs: Get medical advice/attention

P304+P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do – continue rinsing P337+P313 - If eye irritation persists get medical advice/attention

P370+P378 - In case of fire: Use dry chemical, alcohol foam, all purpose AFFF or carbon

dioxide for extinction

Storage Procedures: P405 - Store locked up

P403+P235 - Store in a well ventilated place. Keep cool

Disposal: P501 - Dispose of contents and container in accordance with federal, state, and local

regulations

Other: See section 11 for complete health hazard information.

SECTION 3 COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)	
Benzotriazole derivative	Proprietary	0.1-1.0%	
Alkylated Phenols	Proprietary	1.0 - 3.0%	
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-20%	
Benzene, 1,2,4-trimethyl-	95-63-6	1.0-10%	
Benzene, 1,3,5-trimethyl-	108-67-8	0.1-1.0%	
Cumene	98-82-8	0.1-1.0%	

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

SECTION 4 FIRST AID MEASURES

Eye Contact: Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of

exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice or attention.

Skin Contact: Avoid direct contact. Wear chemical protective clothing, if necessary. Take off

contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash skin with lukewarm, gently flowing water and mild soap until product is removed. Call a doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Discard contaminated clothing. Store contaminated clothing under water and wash before re-use

or discard.

Inhalation: Remove source of exposure or move person to fresh air and keep comfortable for

breathing. If experiencing respiratory symptoms: Call a doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the doctor If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT

Ingestion: If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do N induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

induce vorniting. It vorniting occurs flaturally, lie off your side, in the

Other: No additional information

SECTION 5 FIRE FIGHTING MEASURES

Flash Point: 79℃ by Cleveland Open Cup Tester.

Flammable limits: Not determined.



Safety Data Sheet Toro Premium Fuel Treatment Revision Date: 4/29/15

Extinguishing media:

Use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire.

Special firefighting procedures: DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this

may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes. Wear full

firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Unusual fire & explosion

hazards:

Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. High temperatures may create heavy flammable vapors that may

settle along ground level and low spots to create an invisible fire hazard.

Fires involving this product may release oxides of carbon, phosphorus, nitrogen and Byproducts of combustion:

sulfur; reactive hydrocarbons and irritating vapors.

Autoignition temperature:

Explosion data:

Not determined. Care should always be exercised in dust/mist areas.

Other: Dispose of fire debris and contaminated extinguishing water in accordance with official

regulations.

Not determined.

SECTION 6

ACCIDENTAL RELEASE MEASURES

Spill control procedures (land): Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).

Spill control procedures

(water):

Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-

424-8802).

Waste disposal method: Do not empty into drains. All disposals must comply with federal, state, and local

> regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply

for transporting this material when spilled. See Section 14.

CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste Other:

mixture will be regulated.

SECTION 7

HANDLING AND STORAGE

Keep containers closed when not in use. Do not transfer to unmarked containers. Empty Handling procedures:

> containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation

centers for proper cleaning and reuse.

Handling temperatures should not exceed 60℃ (140°F) to min imize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory

protection. Wash thoroughly after handling.

Store containers away from heat, sparks, open flame, or oxidizing materials. Extended Storage procedures:

storage at excessive temperatures may produce odorous and toxic fumes from product

decomposition.

Additional information: No additional information.



SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

OSHA TWA OSHA STEL ACGIH TWA

Contains highly refined petroleum oil

*5 mg/m³ *10 mg/m³ *5 mg/m³
(PEL)

(TLV)

TWA – Time Weighted Average is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded. STEL – Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time limit is specified.

All base oils, including additive carriers, contain <3.0% DMSO extractable material.

Personal protection: Applicable mainly to persons in repeated contact situations such as packaging of

product, service/maintenance, and cleanup/spill control personnel.

Respiratory protection: None required if ventilation is adequate. Otherwise a respiratory protection program

meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form

dust/mist air purifying respirator.

Eye protection: Eye protection is strongly recommended. Wear safety glasses with side shields or

vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection: Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin

sensitization and absorption.

Other protection: Use of an apron and overboots of chemically impervious materials such as neoprene or

nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of

contaminated leather articles and other materials which cannot be decontaminated.

Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical

methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in

areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where product is

present. Always wash hands and face with soap and water before eating, drinking or

smoking.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless to light yellow fluid.

Odor: Mild, solvent odor.
Odor threshold: Not determined.
pH: Not applicable.
Melting/Freezing point: Not determined.
Initial boiling point: Not determined.
Boiling range: Not determined.

Flash point: 79℃.

Evaporation rate: Not determined.
Flammability: Not determined.
Upper flammable limit: Not determined.
Lower flammable limit: Not determined.

^{*} Exposure limits not defined. Limits used are for, "oil mist".



Safety Data Sheet Toro Premium Fuel Treatment Revision Date: 4/29/15

Vapor pressure: Not determined.

Vapor density: >1.

Relative density: 6.78 lbs/gal at 15.6 C (60.0 F).

Solubility: Negligible in water, miscible in most petroleum solvents.

Partition Coefficient: Not determined.
Auto-ignition temperature: Not determined.
Decomposition temperature: Not determined.
Viscosity: 7 cSt at 40°C.
Other Not applicable.

SECTION 10

STABILITY AND REACTIVITY

Reactivity

Chemical stability: Material is chemically stable at room temperatures and pressure.

Hazardous polymerization: Will not occur.

Conditions to avoid: Avoid high temperatures and product contamination. **Incompatibility with other** Avoid contact with acids and strong oxidizing materials.

materials:

Decomposition products: Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete

combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating

vapors.

Other: Not applicable.

SECTION 11

TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section

 Oral:
 >5000 mg/kg

 Dermal:
 >5000 mg/kg

 Inhalation:
 >20.0 mg/l

Skin irritation: Causes skin irritation

Eye irritation: Causes serious eye irritation **Dermal sensitization:** May cause an allergic skin reaction

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard: Not applicable

Chronic Toxicity

Mutagenicity: Not suspected of causing genetic defects

Carcinogenicity: Not suspected of causing cancer.

Reproductive toxicity: Not expected to have adverse effects on reproduction.

STOT-single exposure: Not expected to have adverse effects.

STOT-repeated exposure: Not expected to have long term adverse effects.

Other: *All data in this section is based off calculations from Part 3 of the Globally Harmonized

System of Classification and Labelling of Chemicals (GHS) utilizing information from the

constituent components.

SECTION 12

ECOLOGICAL INFORMATION

Environmental toxicity

 Fish:
 10 - 100 mg/l.


 Invertebrates:
 10 - 100 mg/l.

 Aquatic plants:
 10 - 100 mg/l.

 Microorganism:
 10 - 100 mg/l.

Persistence/Degradability: This product is not expected to be readily biodegradable.

Bioaccumulation: Not determined.





Mobility in soil:

Other:

Not determined.

All classifications are based on calculations in Part 4 of the Globally Harmonized System

of Classification and Labelling of Chemicals (GHS) utilizing information from the

constituent components.

DISPOSAL CONSIDERATIONS **SECTION 13**

This product unadulterated by other materials can be classified as a non-hazardous Waste disposal:

> waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste

management should be in full compliance with federal, state, and local laws.

Other The transportation, storage, treatment and disposal of RCRA waste material must be

conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14 TRANSPORT INFORMATION

NA1993 Land Transport (DOT):

Proper Shipping Name: Combustible liquid, n.o.s. (light petroleum distillates),3,PG III

Land Transport (TDG): Not regulated for land transport

Proper Shipping Name: Not applicable.

Sea Transport (IMDG): Not regulated for sea transport

Proper Shipping Name: Not applicable.

Not regulated for air transport Air Transport (IATA):

Proper Shipping Name: Not applicable.

Other: Not DOT regulated in packages less than 119 gallons when offered for shipment by

ground.

See 49 CFR for additional requirements for descriptions, allowed modes of transport, and packaging. For more information concerning spills during transport, consult latest DOT Emergency Response Guidebook for Hazardous Materials Incidents, DOT P 5800.3.

SECTION 15 REGULATORY INFORMATION

Federal Regulation

Clean water act/oil: Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Control Act

of 1990, this material is considered an oil. Any spill or discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface

water must be reported. Contact the National Response Center at 800-424-8802.

TSCA: All components of this material are listed in the U.S. TSCA Inventory.

Other TSCA: Not applicable.

Section 302/304 extremely hazardous substances: SARA title III:

None.

Section 311, 312 hazard categorization:

Acute (immediate health effects): YES Chronic (delayed health effects): YES Fire (hazard): YES Reactivity (hazard): NO Pressure (sudden release hazard): NO

Section 313 toxic chemicals:

No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.



CERCLA:

Version:

For stationary/moving sources – reportable quantity (due to): Not hazardous due to the petroleum exclusion.

Safety Data Sheet

Toro Premium Fuel Treatment Revision Date: 4/29/15

State Regulations Right-to-know Other:

Not determined.

A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

SECTION 16	OTHER		
	NFPA 704	NPCA-HMIS	KEY
HEALTH:	2	2	0 = Minimal
FIRE:	2	2	1 = Slight
REACTIVITY:	0	0	2 = Moderate
SPECIFIC HAZARD:	None	N/A	3 = Serious
PROTECTION INDEX:	N/A	В	4 = Severe

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None.