

# iGen2600 SPECIFICATIONS

Gasoline Peak Watts	2600
Gasoline Running Watts	2200
Peak Amps at 120V	21.6 amps
Running Amps at 120V	18.3 amps
AC Voltage	120 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable with WHPC cord (sold separate)	Yes
Engine Horse Power (HP)	3.4 HP
Total Harmonic Distortion (THD)	<3%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Engine Displacement	98cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine Speed	Variable
Engine RPM	Max 4800
Available in True Timber Camo	Yes
Operational Volume	as low as 52 dBA
Spark Plug (included)	Torch E6RTC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140542
Economy Mode Switch	Yes
Built-in Inverter	Yes
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.37 qt. (11.8 oz.)
Oil Capacity (Quarts/Ounces)	.37 qt. (11.8 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	1 gal. (3.8 L)
*Run Time at %25 Load (hrs.)	10 hrs.
*Run Time at %50 Load (hrs.)	8 hrs.
Gasoline Fuel Gauge	Yes

Choke type	Manual
Choke Location	Control Panel
AC Outlets	(1) Duplex 120V 20A (5-20R)
DC Outlets	(1) 12V DC 8A (2) USB 5V
Ground	Floating Neutral
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
Volt Meter	Yes
GFCI Outlets	No
LED Data Center	Yes
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single, molded in case
Wheel Kit	No
Emissions	EPA, CARB
Canada CSA Compliant	No
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years
Commercial Warranty	1 Year
Assembled Length in. (mm)	19.8 in. (503 mm)
Assembled Width in. (mm)	11.4 in. (290 mm)
Assembled Height in. (mm)	17.9 in. (455 mm)
Carton Length in. (mm)	21.5 in. (546 mm)
Carton Width in. (mm)	12.75 in. (324 mm)
Carton Height in. (mm)	18.5 in. (470 mm)
Dry Unit Weight lb. (kg)	48 lb. (21 kg)
Shipping Weight lb. (kg)	56 lb. (24 kg)
UPC	853544008250
GTIN	00853544008250

05302018KD

Specifications are subject to change without notice

\*Run time is estimated and will vary with different applications.

