

WGen9500DF

9500 Watt Open Frame

Dual Fuel (Gas/LPG) Portable Generator

Gas: 9500W Running 12500W Peak | Propane: 8500W Running 11200W Peak



Rugged roll bars for added strength and protection

Fuel gauge on top of 6.6 gal. gas tank



50 State Model

Fuel selector switch allows to easily switch from gas to propane without shutting off the unit

Push-button electric start, lights up green when unit is on

Westinghouse ST Switch (Portable Automatic Transfer Switch) outlet

Heavy duty 457cc OHV 4-Stroke Westinghouse engine

Transfer switch ready 120/240V 50A outlet



Remote start key fob included for starting and stopping generator up to 109 yards away



What Comes in the Box



WGen9500DF

Generator Specifications



Gasoline Running Watts	9500
Gasoline Peak Watts	12500
Gasoline Running Amps	79A @ 120V 35.5A @ 240V
Gasoline Peak Amps	104A @ 120V 52A @ 240V
Propane Running Watts	8500
Propane Peak Watts	11200
Propane Running Amps	71A @ 120V 35A @ 240V
Propane Peak Amps	93A @ 120V 47A @ 240V
AC Voltage	120/240 Volts
AC Frequency	60 Hz
Parallel Capable	No
Total Harmonic Distortion (THD)	<23%
Automatic Voltage Regulator (AVR)	Yes
Low Idle Control	No
Starting System	Electric, Remote, Recoil
Battery Included	Yes
Battery Charger Included	Yes
Remote Start Fob Included	Yes (factory paired)
Remote Start Distance (yards/meters)	109 yd. (100 m.)
Push Button Start	Yes
Mobile App Compatible	No
Engine Displacement	457cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume	As low as 74 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140568
Altitude DF Regulator Assembly (sold separate)	140566
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt. (37.2 oz)
Oil Capacity (Quarts/Ounces)	1.1 qt. (37.2 oz)
Low Oil Shutdown	Automatic
Fuel Type	Propane or Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual

Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	6.6 gal. (25 L)
Run Time at %25 Load (hrs.)	17.5 hrs.
Run Time at %50 Load (hrs.)	12 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Automatic
AC Outlets	(2) Duplex 120V 20A (5-20R), (1) 120/240V 30A (L14-30R), (1) 120/240V 50A (14-50R)
Ground	Neutral Bonded to Frame
Covered Outlets	Yes
Transfer Switch Ready	Yes
Westinghouse Portable Transfer Switch Ready	Yes
Volts, Frequency, Lifetime Hour Meter	Yes
GFCI Outlets	Yes
OSHA Compliant	No
LED Data Center	No
RV Ready Outlet	Yes
Overload Protection (circuit breaker)	Yes
Handle	Yes
Emissions	EPA, CARB
Canada CSA Compliant	No
Heavy Duty Wheel Kit Included	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years
Commercial Warranty	1 Year
Assembled Length in. (mm)	27.2 in. (691 mm)
Assembled Width in. (mm)	26.5 in. (673 mm)
Assembled Height in. (mm)	26 in. (660 mm)
Carton Length in. (mm)	31 in. (787 mm)
Carton Width in. (mm)	21.5 in. (546 mm)
Carton Height in. (mm)	23 in. (584 mm)
Dry Unit Weight lb. (kg)	220 lb. (98kg)
Shipping Weight lb. (kg)	235 lb. (103kg)
UPC	853544008298
GTIN	00853544008298

03122019KD

©2019 Westinghouse Outdoor Power Equipment
Specifications are subject to change without notice
777 Manor Park Dr., Columbus, OH 43228

/wpowereq

/WestinghouseProducts

WestinghouseOutdoorPower.com

**Have questions? Contact our team
at service@wpowereq.com or call
855.944.3571**

®WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF
are trademarks of Westinghouse Electric Corporation. Used
under license by Westinghouse Outdoor Power Equipment.
All Rights Reserved.

