

# iPro2500



50 State and  
Canada Model



## Westinghouse

## 2500 Watt Digital Inverter Gasoline Portable Generator

2200 Running Watts | 2500 Peak Watts

<3% THD  
SINE WAVE OUTPUT



Built-in carry handle for easy transportation

Fuel efficient, 1 gallon fuel tank that runs 10 hrs at 25% load

Added air vents to keep unit cool while running

OSHA compliant 120V 20A 5-20R GFCI outlet

Two 5V USB ports for charging sensitive electronics such as phones or tablets



Dependable 3.4 HP 98cc OHV 4-Stroke Westinghouse engine



Double-insulated acoustic enclosure and low tone mufflers to reduce operating noise



JOB SITE  
APPLICATIONS

ENGINE/FUEL  
CONTROL  
SWITCH

LOW OIL, OVERLOAD  
& OUTPUT READY  
INDICATOR LIGHTS

20A CIRCUIT  
BREAKER

120V AC 20A 5-20R  
GFCI OUTLETS  
WITH COVER

GROUND  
NEUTRAL BONDED TO FRAME  
DC SYSTEM FLOATING

OVERLOAD  
RESET

5V DC USB  
PORTS  
WITH  
COVER



What Comes in the Box



# iPro2500

## Inverter Generator Specifications



Gasoline Peak Watts	2500
Gasoline Running Watts	2200
Peak Amps at 120V	20.8 amps
Running Amps at 120V	18.3 amps
AC Voltage	120 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable with WHPC cord (sold separate)	Yes
Engine Horse Power (HP)	3.4 HP
Total Harmonic Distortion (THD)	<3%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Engine Displacement	98cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine Speed	Variable
Engine RPM	Max 5200
Operational Volume at 25% Load	52 dBA
Operational Volume at 50% Load	59 dBA
Spark Plug (included)	Torch E6RTC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140542
Economy Mode Switch	Yes
Built-in Inverter	Yes
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.37 qt. (11.8 oz.)
Oil Capacity (Quarts/Ounces)	.37 qt. (11.8 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel
Fuel Tank Capacity (Gallons/Liters)	1 gal. (3.8 L)

Run Time at %25 Load (hrs.)	10 hrs.
Run Time at %50 Load (hrs.)	8 hrs.
Gasoline Fuel Gauge	No
Choke type	Manual
Choke Location	Control Panel
AC Outlets	(1) Duplex 120V 20A GFCI (5-20R)
DC Outlets	(2) 5V USB ports
Ground	Neutral Bonded to Frame
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
Volt Meter	No
GFCI Outlets	Yes
LED Data Center	No
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single, molded in case
Wheel Kit	No
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs.
Commercial Warranty	6 Months or 1000 hrs.
Assembled Length in. (mm)	19.75 in. (501.65 mm)
Assembled Width in. (mm)	10.5 in. (266.7 mm)
Assembled Height in. (mm)	18.25 in. (463.55 mm)
Carton Length in. (mm)	21.5 in. (546 mm)
Carton Width in. (mm)	12.75 in. (323.85 mm)
Carton Height in. (mm)	18.75 in. (490 mm)
Dry Unit Weight lb. (kg)	48 lb. (21 kg)
Shipping Weight lb. (kg)	56 lb. (24 kg)
UPC	855464003995
GTIN	00855464003995

07202018SC  
 ©2018 Westinghouse Portable Power  
 Specifications are subject to change without notice  
 Westinghouse Portable Power  
 777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team  
 at [service@wpowereq.com](mailto:service@wpowereq.com) or call  
 855.944.3571**



/wpowereq



/WestinghouseProducts



WestinghousePortablePower.com

