quality . service innovation . integrity

Model 95





B "The color green is a registered trademark of Zoeller Pump Co."

Features

This "Flow-Mate" model submersible pump is designed for use in residential or light commercial dewatering applications and can be used to transfer groundwater or effluent. This durable cast iron pump includes a powder coated epoxy finish to prevent corrosion and is designed to provide great heat dissipation from the motor, ensuring a long service life. As with every Zoeller pump, each one is 100% pressure-tested, submerged and run to ensure quality and reliability for years of trouble-free performance! This attention to detail is an inherent feature of every pump, making it one of the most reliable in the industry.

- For nonautomatic pumps, variable level control systems and containers of various sizes are available for longer cycles.
- Includes a stainless steel handle for easy installation and removal.
- Hermetically sealed to be watertight, dust-tight, and completely submersible.

Reserve Powered Design: For unusual conditions, a reserve safety factor is engineered into the design of every pump.

Specifications

Motor Characteristics

Motor	1/2
Voltage	115
Phase	1 Ph
Hertz	60 Hz
RPM	3450
Туре	Permanent split capacitor
Insulation	Class B
Amps	10.5

Pump Characteristics

Operation Auto On/ Off Points Discharge Size Solids Handling Cord Length Cord Type Max Head Max Flow Rate Max Operating Temp Cooling Motor Protection Automatic 9-1/2" (24 cm) / 2-1/2" (6.4 cm) 1-1/2" NPT 1/2" (12 mm) spherical solids 15' (4.6 m) UL listed, 3-wire, grounded plug 26' (7.9 m) 80 GPM (303 LPM) 130° F (54° C) Oil filled Auto reset thermal overload

Materials Characteristics


Cap Motor Housing Pump Housing Base Upper Bearing Lower Bearing Mechanical Seals Impeller Type Impeller Hardware Motor Shaft Gasket Cast iron Cast iron Cast iron Cast iron Sleeve bearing Ball bearing Carbon and ceramic Non-clogging vortex Engineered thermoplastic Stainless steel AISI 1215 cold rolled steel Neoprene






FM3001 Updated 0117

Model 95





Model

Model Number	Mode	Volts	Phase	Amps	HP	Hz
M95	Automatic	115	1	10.5	1/2	60

Your Peace of Mind is Our Top Priority® 3649 Cane Run Rd | Louisville, KY 40211 USA +1 502-778-2731 | 1-800-928-7867 | Fax: +1 502-774-3624 www.zoeller.com

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies. Copyright Zoeller Company. All rights reserved.